

Plafit GT3

REGULATIONS CURRENT @ 1 Jan 2025 ONWARDS PENDING UPDATES

1.0 BODY

- 1.1 Must use any ACE/Abarth Lexan GT3 body set (see current listing below).
- 1.2 Must be cut to the manufacturer's cut lines including the wheel arches.
- 1.3 Must mount wing minimum of 3mm above rear of the body but no higher than the roof.
- 1.4 Must use a vacuum formed driver interior painted a minimum 3 colours.
- 1.5 Must have an opaque livery with three race numbers.
- 1.6 Must cover complete chassis/running gear when viewed from above or through any window.

BODY LIST – CHECK 'ACE HOBBIES' WEBSITE FOR ANY UPDATES

ITEM NO.	DESCRIPTION	CLASS
24010	Chevrolet Camaro GT3	LGT3
24011	Aston Martin Vantage GT3	LGT3
24012	Audi R8 LMS	LGT3
24013	Bentley Continental GT3	LGT3
24014	BMW M6 GTLM	LGT3
24015	Corvette C7R	LGT3
24016	Ferrari 458 GT3	LGT3
24017	Lamborghini Huracan GT3	LGT3
24018	McLaren 650S GT3	LGT3
24019	Mercedes SLS AMG GT3	LGT3
24020	Nissan GT-R Nismo GT3	LGT3
24021	Porsche 991 RSR GT3	LGT3
24022	SRT Viper GT3	LGT3
24023	Honda NSX GT3	LGT3
24030	Volvo GT3	LGT3
24031	Ford Mustang GT3	LGT3

2.0 CHASSIS

- 2.1 Must use Plafit SLP2 Short Can (1801C) or Long Can (1801SL) chassis plate.
Note:- chassis plate dimensions must remain as manufactured and must not be altered EXCEPTING the rear spur gear hole may be extended rearward for larger spurs.
- 2.2 Any motor bracket, motor stay and bearing holders.
- 2.3 Any carbon fibre parts.
- 2.4 Must only use screws to install motor.
- 2.5 Weight may be added.

3.0 CLEARANCE

- 3.1 1.0mm min under entire car.

4.0 FRONT & REAR AXLE, BEARINGS & SPUR

- 4.1 Must be one piece 3mm axle using any bearings and max spur of 83mm

5.0 FRONT WHEELS

- 5.1 Must be non independent aluminium hubs with 3D inserts. Tyres may be sealed.
- 5.2 Must have min width 6mm and min diameter 24mm.

6.0 REAR WHEELS

- 6.1 Must use aluminium hubs with 3D inserts using Plafit or Scaleauto tyres.
- 6.3 Must have max width 16mm and min diameter 25mm.

7.0 GEARS

- 7.1 Must use M50 10T pinion with any size plastic spur.

8.0 MOTOR

- 8.1 Unmodified sealed and marked Cheetah 4 motor or as nominated by Raceway or Event.

9.0 WEIGHT

- 9.1 160gms minimum.